



# L.T.F. Low Voltage Dimmable Power Supply



## TA60WD12LEDRE No-Load Electronic Transformer



<b>Efficiency</b>	higher than 85%
<b>Power Factor</b>	>95%
<b>Case TC</b>	90°C Max.
<b>Protection</b>	Input/Output
<b>Storage</b>	-30°C/+90°C
<b>Class</b>	Class 2 Power Supply
<b>Dimming</b>	ELV Dimmable
<b>Optional Dimming</b>	0-10V Dimming



RoHS



\* Ask for more information

### FEATURES

- No load technology, works with both Halogen & LED AC loads \*\*
- Isolated output power per NEC and UL safety requirements
- UL recognized/listed Class 2 power supply, meets UL 2108 requirements
- Auto-reset; Short circuit, Overload and Thermal protection
- Soft start
- 0-10V and ELV Dimmable
- Low profile, small compact design to fit in most enclosures

### ELECTRICAL SPECIFICATIONS

Model #	Wattage	Input Voltage	Output Voltage	Load Type	Dimming
TA60WD12LEDRE	60W	120V AC, 0.5A 50/60Hz	12V DC	LED Strips, LED Bulbs, Incandescent & Halogen Bulbs	ELV Dimmable

### MECHANICAL SPECIFICATIONS

Form Factor	Dimensions
"G2"	233mm x 49mm x 85.5mm

### G2 (-RE) REMOTE INDOOR ENCLOSURE

